





## Spot 120 Dali Version

Spot 120 Dali Version



h(m)	E(lx)	D(m)
1	11417	0.19
2	2854	0.37
3	1269	0.56
4	714	0.75
5	457	0.93



<b>Number of heads</b>	1
<b>Mountings</b>	Track
<b>Lamp category</b>	LED
<b>Colour temperature</b>	2700K
<b>CRI</b>	90
<b>Lumen</b>	539 lm
<b>Voltage (V)</b>	48
<b>Environment</b>	Indoor

<b>LED type</b>	Power LED
<b>Aiming</b>	Adjustable
<b>Light Distribution</b>	Symmetric
<b>Beam Angle</b>	11

<b>Transformer Availability</b>	Separate item
<b>Transformer Mounting</b>	Remote
<b>Transformer Type</b>	Electronic dimmable DALI
<b>Emergency</b>	Without
<b>Insulation Class</b>	III
<b>Lamp Holder</b>	LED
<b>Dimmable</b>	Yes

**Length** 178

<b>Colors</b>	<ul style="list-style-type: none"> <li>● 03.8052.05.DA - Polished Aluminium</li> <li>● 03.8052.14.DA - Black</li> <li>● 03.8052.40.DA - White</li> </ul>
---------------	--

**Certificates**



**Note**

Accessories included (honeycomb and screening crosspiece).

Only compatible with  
DALI, 1-10V, FLOS SMART  
CONTROL profile version.