




## Spot 90 Dimmable 1-10V


Spot 90 Dimmable 1-10V



Beam Angle: 14°

h(m)	E(lx)	D(m)
1	5601	0.25
2	1400	0.49
3	622	0.74
4	350	0.98
5	224	1.23

Luminous flux luminaire  
428 lm



<b>Number of heads</b>	1
<b>Mountings</b>	Track
<b>Lamp category</b>	LED
<b>Colour temperature</b>	2700K
<b>CRI</b>	90
<b>Lumen</b>	428 lm
<b>Voltage (V)</b>	48
<b>Environment</b>	Indoor

<b>LED type</b>	Power LED
<b>Aiming</b>	Adjustable
<b>Light Distribution</b>	Symmetric
<b>Beam Angle</b>	14

<b>Transformer Availability</b>	Separate item
<b>Transformer Mounting</b>	Remote
<b>Emergency</b>	Without
<b>Insulation Class</b>	III
<b>Lamp Holder</b>	LED
<b>Dimmable</b>	Yes

<b>Length</b>	178
---------------	-----

<b>Colors</b>	<ul style="list-style-type: none"> <li>● 03.8042.05.1V - Polished Aluminium</li> <li>● 03.8042.14.1V - Black</li> <li>● 03.8042.40.1V - White</li> </ul>
---------------	--

### Certificates



### Note

Accessories included  
(honeycomb and  
screening crosspiece).  
Only compatible with

DALI, 1-10V, FLOS SMART  
CONTROL profile version.