




## UT Downlight Trim Ø86 Dali Version


UT Downlight Trim Ø86 Dali Version



Beam Angle: 12°

h(m)	E(lx)	D(m)
1	29106	0.21
2	7277	0.41
3	3234	0.62
4	1819	0.82
5	1164	1.03

Luminous flux luminaire  
2259 lm



<b>Number of heads</b>	1
<b>Mountings</b>	Ceiling recessed
<b>Lamp category</b>	LED
<b>Colour temperature</b>	3000K
<b>CRI</b>	80
<b>Lumen</b>	2259 lm
<b>Voltage (V)</b>	36
<b>Environment</b>	Indoor

<b>LED type</b>	LED array
<b>Aiming</b>	Adjustable
<b>Light Distribution</b>	Symmetric
<b>Beam Angle</b>	12

<b>Transformer Availability</b>	Included
<b>Transformer Mounting</b>	Remote
<b>Frequency</b>	50/60
<b>Emergency</b>	Without
<b>Insulation Class</b>	II
<b>Lamp Holder</b>	LED
<b>Dimmable</b>	Yes


**Recessed Depth** 176

<b>Colors</b>	● 09.4910.14ADA - Black
	● 09.4910.30ADA - White

**Certificates**



## UT Downlight Trim Ø86 Dali Version



---

Elliptical lens  
08.8163.68



---

Flood lens  
08.8175.68



---

Honeycomb  
08.8495.14



---

Holding ring  
08.8410.00



---

Screening crosspiece  
08.8411.00