




UT Downlight Trim Ø57 Dali Version


UT Downlight Trim Ø57 Dali Version



Beam Angle: 11°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 14508 | 0.19 |
| 2 | 3627 | 0.39 |
| 3 | 1612 | 0.58 |
| 4 | 907 | 0.77 |
| 5 | 580 | 0.97 |

Luminous flux luminaire
1295 lm



| | |
|---------------------------|------------------|
| Number of heads | 1 |
| Mountings | Ceiling recessed |
| Lamp category | LED |
| Colour temperature | 3000K |
| CRI | 80 |
| Lumen | 1295 lm |
| Voltage (V) | 220 |
| Environment | Indoor |

| | |
|---------------------------|------------|
| LED type | LED array |
| Aiming | Adjustable |
| Light Distribution | Symmetric |
| Beam Angle | 11 |

| | |
|---------------------------------|--------------------------|
| Transformer Availability | Included |
| Transformer Mounting | Remote |
| Transformer Type | Electronic dimmable DALI |
| Frequency | 50/60 |
| Emergency | Without |
| Insulation Class | II |
| Lamp Holder | LED |
| Dimmable | Yes |

| | |
|---------------|-------------------------|
| Colors | ● 09.4510.14ADA - Black |
| | ● 09.4510.30ADA - White |

| | |
|---------------------|--|
| Certificates | |
|---------------------|--|

Note Screening crosspiece, lenses and Honeycomb directly installable on the head of the luminaire

without needing any
fastening accessory.
Installation compatible
with Honeycomb + Lense
at the same time.

UT Downlight Trim Ø57 Dali Version



Honeycomb
08.8428.00



Flood lens
08.8432.00



Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.00