




UT Downlight Trim Ø57 Non Dimmable


UT Downlight Trim Ø57 Non Dimmable



Beam Angle: 11°

h(m)	E(lx)	D(m)
1	14508	0.19
2	3627	0.39
3	1612	0.58
4	907	0.77
5	580	0.97

Luminous flux luminaire
1295 lm



Number of heads	1
Mountings	Ceiling recessed
Lamp category	LED
Colour temperature	3000K
CRI	80
Lumen	1295 lm
Voltage (V)	220
Environment	Indoor

LED type	LED array
Aiming	Adjustable
Light Distribution	Symmetric
Beam Angle	11

Transformer Availability	Included
Transformer Mounting	Remote
Transformer Type	Electronic
Frequency	50/60
Emergency	Without
Insulation Class	II
Lamp Holder	LED
Dimmable	No

Colors	● 09.4510.14A - Black
	● 09.4510.30A - White

Certificates	
---------------------	--

Note	Screening crosspiece, lenses and Honeycomb
-------------	--

directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with Honeycomb + Lense at the same time.

UT Downlight Trim Ø57 Non Dimmable



Honeycomb
08.8428.00



Flood lens
08.8432.00



Elliptical lens
08.8431.00



Snoot shielding cone
08.0526.00