

CAMOUFLAGE 240 MM

Beam angle	151°
Mounting	Wall surface
Lamps description	Mid-Power Led: 12W - 1563 lm ≠ FIXT 944 lm - 4000K/CRI 80 - 220-240V
Environment	Indoor, Outdoor
Notes	We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

Technical description

Dissipating aluminum body with diffuser in transparent polycarbonate. The Crema d'Orcia and Basaltina stone finishes are made by fastening high-strength, high-resistance adhesive to a stone plate created by means of mechanical machining from a solid block. The concrete finishing is made by fastening a poured cement plate reinforced with fiberglass using a single component high strength, high-resistance adhesive. The Primer version is painted after installation with normal water-based colors (tempera, stucco, water-based paints) to ensure maximum uniformity with the architecture. The aluminum versions are finished with a high-resistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is applied with a double layer with epoxy powders according to the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation. Upon commercial and technical evaluation, it is possible to create customized versions with other materials on request.

ELECTRICAL

Transformer type	Electronic
Transformer availability	Included
Transformer mounting	Integral
Emergency	Without
Voltage (V)	220/240

PHYSICAL

Aiming	Fixed
Diameter (mm)	240
Weight (kg)	max 1,50
Number of heads	1




Camouflage 240 mm

designed by Piero Lissoni

Collection of products for outdoor use, for wall installation with LED light source. Integrated 220/240V power source. Supplied with a 1000 mm section of outgoing neoprene cable. Version 110V upon request.


	FI317000	Primer
	FI317001	White
	FI317006	Grey
	FI317018	Deep brown
	FI317030	Black
	FI317033	Anthracite
	FI317087	Basaltina Stone
	FI317089	Concrete
	FI317090	Crema d'orcica stone

DIMENSIONS



*Concrete, crema d'orcica, basaltina H = 48 mm.

CERTIFICATIONS





Camouflage 240 mm . Lamps



Mid-Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Camouflage 240 mm

designed by Piero Lissoni

Collection of products for outdoor use, for wall installation with LED light source. Integrated 220/240V power source. Supplied with a 1000 mm section of outgoing neoprene cable. Version 110V upon request.

	FI317000	Primer
	FI317001	White
	FI317006	Grey
	FI317018	Deep brown
	FI317030	Black
	FI317033	Anthracite
	FI317087	Basaltina Stone
	FI317089	Concrete
	FI317090	Crema d'orcina stone

DIMENSIONS



*Concrete, crema d'orcina, basaltina H = 48 mm.

CERTIFICATIONS

