WEVER & DUCRÉ
LIGHTING

TRAM
1.0 ROUND

747368B5

Project

Type

Notes

Quantity

Date

GENERAL
Ceiling
Surface
Jet Black
IP65
Exterior
415 lm
9005 [a]

LED
3000 K
CRI 90
L70 / 50000 h
3-step binning

OPTICAL
flood
Beam angle 38°

PHYSICAL
Diameter 50 mm
Height 75 mm
0.24 kg

ELECTRICAL
phase-cut dim
220 - 240 V
Total connected power 6 W
PC1
Safety distance 0.3 m

[a] RAL Palette colors may deviate slightly due to production conditions.



LIGHT DISTRIBUTION



['747368B5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.

December 15, 2020

© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

WEVER & DUCRÉ
LIGHTING

TRAM
1.0 ROUND

747368B5

CONE DIAGRAM

38°

h (m)	E0° (lx)	ø (m)
1	854	0.69
2	214	1.38
3	94	2.06
4	53	2.75
5	34	3.44

['747368B5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com